



SLC Power Supply CV 24V 50W PWM 1-10V

19/06/2023

S32041



Product description

50W power supply with 1-10V current-controlled PWM-dimming. Compatible with all types of 1-10V signal and controllers. Can also be controlled with PushDim

50W power supply with 1-10V current-controlled PWM-dimming. Compatible with all types of 1-10V signal and controllers. Can also be controlled with PushDim Protection against overload, short circuit and overheating. For 24V LED-strips and other products with 24V operating voltage

Technical data

Model	Static
Dimming 0-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming phase cut-on	No
Dimming RF	No
Dimming Touch and Dim	No
Dimming with push-button	Yes
Housing	Plastic housing
Suitable for constant voltage	Yes
Output current	208 - 2080 Milliampere
Degree of protection (IP)	IP20
Length	210 Millimetre
Dimming Touch and Dim Dimming with push-button Housing Suitable for constant voltage Output current Degree of protection (IP)	No Yes Plastic housing Yes 208 - 2080 Milliampere IP20

No
Yes
No
24 - 24 Volt
5 - 50 Watt
II
50 Millimetre





Height	32 Millimetre
Number of LED Output Channels	1
Mono	Yes
RGB	No
Electrical connection (Out)	L'N quick connection
Frequency range (Hz)	50 - 60
Strain relief	Yes
Operating temperature	-20°C ~ +45°C
Dimming method	Pulse Width Modulation (PWM)
Brand	SLC
Produced by	The Light Group

Output type	Constant voltage (CV)
Output power per channel (W)	5 - 50
Tunable White	No
RGBW	No
Input voltage (V)	200 - 240
Power factor	0,95
Exterior color	White
Expected lifetime (Hours) (Ta 45°C)	50000
Dimming interface	1-10V, PushDim
GTIN	7070938057332
HS Code	85041080